

- NOTES:
1. MAXIMUM PERMISSIBLE OUT OF SQUARE OF PIN TO MOULDING TO BE 0.10mm IN ANY DIRECTION.
 2. CONTACT LEG VARIATION ON COMPLETE ASSEMBLY NOT TO EXCEED 0.10mm.


THIS SKETCH IS FOR
QUOTATION PURPOSES
ONLY

SPECIFICATION:
 MATERIAL:
 MOULDING = HIGH TEMPERATURE
 NYLON 6T, UL94V-0, BLACK
 PINS = BRASS
 FINISH:
 PINS: SEE BOX BELOW
 ELECTRICAL:
 CURRENT RATING = 1A MAX
 CONTACT RESISTANCE = 30 mΩ MAX
 INSULATION RESISTANCE = 5,000 MΩ MIN
 DIELECTRIC STRENGTH = 500V AC/DC
 ENVIRONMENTAL:
 TEMPERATURE RANGE = -55°C TO +105°C
 PACKING:
 BAG

FINISH	
(TICK APPLICABLE):	
☐	100% TIN
☐	GOLD

DATE OF SKETCH:
REQUESTED BY:

No. OF CONTACTS PER ROW:



HARWIN		
HARWIN INC U.S.A. TEL: (812) 542 2540 FAX: (812) 542 2541	HARWIN PLC U.K. TEL: 023 9231 4545 FAX: 023 9231 4590	HARWIN PTE SINGAPORE TEL: 65 6779 4909 FAX: 65 6779 3868

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.	TOLERANCES X. = $\pm 1\text{mm}$ X.X = $\pm 0.25\text{mm}$ X.XX = $\pm 0.10\text{mm}$ X.XXX = $\pm 0.01\text{mm}$ ANGLES = $\pm 5^\circ$ UNLESS STATED
---	---

TITLE: 1.27 x 2.54mm PITCH SIL EXTENDED PC TAIL PIN HEADER VARIANT	DRAWING No.: M52- E
SHT 1 OF 1	