



Harwin Test Report Summary

HT01201

Mechanical Testing of Datamate (M80 Series)
L-Tek Horizontal Male SMT Contacts

Datamate

A decorative graphic at the bottom of the page consisting of multiple thin, red, wavy lines that flow from the left side towards the right, creating a sense of motion and depth.

Introduction.

1.1. Description and Purpose.

The Harwin Datamate (M80 Series) connector is manufactured to the requirements of BS9525-F0033. The following tests were carried out to confirm that the new design of stamped contacts for use in Datamate L-Tek Male Horizontal SMT connectors would be comparable with the rest of the range for contact retention. The results of testing to confirm insertion force, withdrawal force and contact resistance in L-Tek can be read over from the J-Tek results, documented in Harwin Test Summary HT010XX.

1.2. Conclusion.

The following test data has been taken from Harwin test report C41/06. Both stamped contacts easily met the required standards, and are therefore approved for use as Datamate contacts.

2. Test Method, Requirements and Results.

2.1. List of Test Samples.

- a) M80-6650442 – 4-way male Horizontal SMT J-Tek connector, incorporating stamped contacts M80-2340042 and M80-2350042
- b) M80-6652042 – 20-way male Horizontal SMT J-Tek connector, incorporating stamped contacts M80-2340042 and M80-2350042
- c) M80-6653442 – 34-way male Horizontal SMT J-Tek connector, incorporating stamped contacts M80-2340042 and M80-2350042

2.2. Specification Parameters.

The BS9525-F0033 requirement for contact retention within a moulding is 10N minimum.

2.3. Results.

	M80-6650442		M80-6652042		M80-6653442	
Contact	M80-2340042	M80-2350042	M80-2340042	M80-2350042	M80-2340042	M80-2350042
Minimum	17.98N	15.40N	15.21N	11.32N	15.60N	13.68N
Maximum	19.69N	17.80N	18.88N	17.52N	22.93N	21.00N
Average	18.55N	16.60N	16.26N	14.46N	19.38N	18.14N