

Gecko Screw-Lok Connectors

GECKO SCREW-LOK

Male Vertical Throughboard

- Stainless steel screw fixing to mate with applicable female connector.
- Order nuts for board-mount separately - see bottom of page.
- 2A current capacity, resists high vibration and shock.
- Withstands extremes of temperature: -65°C to +150°C.



WITHOUT BOARD MOUNT	WITH BOARD MOUNT																						
<p style="text-align: center;">Recommended PC Board Pattern</p>	<p style="text-align: center;">Recommended PC Board Pattern</p>																						
<table border="1" style="margin: auto;"> <thead> <tr style="background-color: #e6f2ff;"> <th colspan="2">CALCULATION</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>$B + 12.7$</td> </tr> <tr> <td>B</td> <td>$0.625 \times (\text{Total No. of contacts} - 2)$</td> </tr> <tr> <td>C</td> <td>$B + 7.8$</td> </tr> <tr> <td>D</td> <td>$B + 1.8$</td> </tr> </tbody> </table>		CALCULATION		A	$B + 12.7$	B	$0.625 \times (\text{Total No. of contacts} - 2)$	C	$B + 7.8$	D	$B + 1.8$												
CALCULATION																							
A	$B + 12.7$																						
B	$0.625 \times (\text{Total No. of contacts} - 2)$																						
C	$B + 7.8$																						
D	$B + 1.8$																						
HOW TO ORDER																							
<p style="font-size: 1.2em; font-weight: bold;">G125 - M V1 XX 05 MX X</p>																							
<table border="1" style="width: 100%;"> <thead> <tr style="background-color: #e6f2ff;"> <th colspan="2">SERIES CODE</th> </tr> </thead> <tbody> <tr style="background-color: #e6f2ff;"> <th colspan="2">TYPE</th> </tr> <tr> <td style="width: 20px;">V1</td> <td>3mm Throughboard</td> </tr> </tbody> </table> <table border="1" style="width: 100%;"> <thead> <tr style="background-color: #e6f2ff;"> <th colspan="2">TOTAL NO. OF CONTACTS</th> </tr> </thead> <tbody> <tr> <td style="width: 20px;">06, 10, 12, 16, 20, 26, 34, 50</td> <td></td> </tr> </tbody> </table>	SERIES CODE		TYPE		V1	3mm Throughboard	TOTAL NO. OF CONTACTS		06, 10, 12, 16, 20, 26, 34, 50		<table border="1" style="width: 100%;"> <thead> <tr style="background-color: #e6f2ff;"> <th colspan="2">PACKAGING</th> </tr> </thead> <tbody> <tr> <td style="width: 20px;">R</td> <td>Tape & Reeled</td> </tr> <tr> <td>P</td> <td>Loose</td> </tr> </tbody> </table> <table border="1" style="width: 100%;"> <thead> <tr style="background-color: #e6f2ff;"> <th colspan="2">SCREW-LOK</th> </tr> </thead> <tbody> <tr> <td style="width: 20px;">M1</td> <td>Internal Thread</td> </tr> <tr> <td>M2</td> <td>With 5mm Board Mount Stud</td> </tr> </tbody> </table>	PACKAGING		R	Tape & Reeled	P	Loose	SCREW-LOK		M1	Internal Thread	M2	With 5mm Board Mount Stud
SERIES CODE																							
TYPE																							
V1	3mm Throughboard																						
TOTAL NO. OF CONTACTS																							
06, 10, 12, 16, 20, 26, 34, 50																							
PACKAGING																							
R	Tape & Reeled																						
P	Loose																						
SCREW-LOK																							
M1	Internal Thread																						
M2	With 5mm Board Mount Stud																						
REQUIRED HARDWARE																							
<p style="text-align: center;">Hexagonal Board Mount Nut</p> <table border="1" style="width: 100%; margin-top: 10px;"> <thead> <tr style="background-color: #e6f2ff;"> <th>ORDER CODE</th> </tr> </thead> <tbody> <tr> <td>G125-4500000B</td> </tr> </tbody> </table>	ORDER CODE	G125-4500000B	<p style="text-align: center;">Slotted Board Mount Nut</p> <table border="1" style="width: 100%; margin-top: 10px;"> <thead> <tr style="background-color: #e6f2ff;"> <th>ORDER CODE</th> </tr> </thead> <tbody> <tr> <td>G125-4510000B</td> </tr> </tbody> </table>	ORDER CODE	G125-4510000B																		
ORDER CODE																							
G125-4500000B																							
ORDER CODE																							
G125-4510000B																							

All dimensions in mm.

Patent Published