
Customer Information Sheet





CONTACT No WIRE COLOUR BLACK BROWN RED 3 ORANGE YELLOW 5 6 GREEN BLUE 8 VIOLET 9 GREY WHITE 10

WIRE COLOURS REPEAT IN ABOVE ORDER FOR CONNECTOR ASSEMBLIES OVER 10 CONTACTS.

OBSOLETE 32AWG Variants Last Time Buy 21-Aug-2020

- I. CABLE ASSEMBLIES WILL BE PACKED IN BAGS OF 10.
- 2. FOR COMPLETE SPECIFICATION, SEE COMPONENT SPECIFICATION COO5XX AND CO49XX (LATEST ISSUES).

DIMENSION	MEASUREMENT		
DIM 'A'	TOTAL No. OF CONTACTS – 2.00		
DIM 'B'	TOTAL No. OF CONTACTS + 5.00		
DIM 'C'	TOTAL No. OF CONTACTS + 10.0		
EVANDLE DADT H			

EXAMPLE PART No.:

10 CONTACT CONNECTOR WITH 150mm OF 22AWG WIRE =

M80-FC11005F1-01501 50 CONTACT CONNECTOR WITH 450mm OF 26AWG WIRE =

M80-FC35005FI-0450L

M	THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARMIN	TOLERANCES X. = ±1mm X.X = ±0.50
	TOTAL No. OF CONT 06, 10, 14, 20, 2 34, 42, 50.	
	6 = 32AWG (EXTRA	SMALL BORE)

THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.

-7.55 MAX-

WIRE AWG:

ORDER CODE:

= 22AWG (LARGE BORE)

2 = 24AWG (SMALL BORE)

3 = 26AWG (SMALL BORE)

4 = 28AWG (SMALL BORE)

X. = ±1mm X.X = ±0.50mn $X.XX = \pm 0.20$ mm $X.XXX = \pm 0.01$ mm ANGLES = ±5° UNLESS STATED

MATERIAL: SEE ABOVE

SEE ABOVE

DIM 'D' LENGTH:

0060 = 60 mm MIN

9999 = 9999mm MAX

(SEE TABLE FOR EXAMPLES)

M80 FEMALE SINGLE-ENDED CABLE ASSEMBLY

APPROVED:

CUSTOMER REF.:

ASSEMBLY DRG:

01.06.20 30039

R.PORTLOCK

R.ALEXANDER

R.PORTLOCK

DATE CN/CO

OF2

DRAWING NUMBER:

www.harwin.com

technical@harwin.com

FINISH: S/AREA:

SECTION X-X

M80-FC<u>XXX</u>68FI-<u>XXXX</u>L

M80-FCXXX68FI-XXXXL