

Material Declaration for G125-224XX96XX

Product Information	
Part Number:	G125-224XX96F1
Part Description:	Gecko 1.25mm Female
Part Weight (g):	(0.0162 * XX) + 0.649

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	n/a
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #	
Jackscrews - Stainless Steel	0.254	10%	Iron	7439-89-6	
	0.0594	4%	Chromium (Metallic)	7440-47-3	
	0.0297	4%	Nickel	7440-02-0	
	0.00231	0.8%	Copper	7440-50-8	
	0.000826	0.5%	Sulphur	7704-34-9	
	0	0.000396g max	Carbon (impurity only)	7440-44-0	
	0	0.0033g max	Silicon (impurity only)	7440-21-3	
	0	0.0066g max	Manganese (impurity only)	7439-96-5	
	0	0.000198g max	Phosphorus (impurity only)	7723-14-0	
	0	0.0033g max	Molybdenum (impurity only)	7439-98-7	
	0	0.000364g max	Nitrogen (impurity only)	7727-37-9	
	0	0.00066g max	Niobium (impurity only)	7440-03-1	
	0	0.00033g max	Titanium (impurity only)	7440-32-6	
	Jackscrew Retainers - Stainless Steel	0.121	10%	Iron	7439-89-6
		0.03	4%	Chromium (Metallic)	7440-47-3
0.015		4%	Nickel	7440-02-0	
0.00117		0.8%	Copper	7440-50-8	
0.000416		0.5%	Sulphur	7704-34-9	
0		0.0002g max	Carbon (impurity only)	7440-44-0	
0		0.00167g max	Silicon (impurity only)	7440-21-3	
0		0.00333g max	Manganese (impurity only)	7439-96-5	
0		0.0001g max	Phosphorus (impurity only)	7723-14-0	
0		0.00167g max	Molybdenum (impurity only)	7439-98-7	
0		0.000184g max	Nitrogen (impurity only)	7727-37-9	
0		0.000334g max	Niobium (impurity only)	7440-03-1	
0		0.000166g max	Titanium (impurity only)	7440-32-6	
Moulding (total weight) Containing:		(0.0162 * XX) + 0.135	5%	30% GF Nylon 4T	
		(0.00907 * XX) + 0.0756	5%	Nylon 4T	103945-40-0
	(0.00486 * XX) + 0.0405	5%	30% Glass Fibre	65997-17-3	
	(0.00203 * XX) + 0.0169	5%	Organic phosphorus compound	-	
	(0.000243 * XX) + 0.00203	5%	Other Additives	-	
Does not contain:			Antimony		
			Other Brominated Flame Retardants		
			Red Phosphorus		

Material Declaration for G125-224XX96XX

Product Information	
Part Number:	G125-224XX96F2
Part Description:	Gecko 1.25mm Female
Part Weight (g):	(0.0162 * XX) + 0.466

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	n/a
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Screw-Lok Nuts - Stainless Steel	0.239	10%	Iron	7439-89-6
	0.0592	4%	Chromium (Metallic)	7440-47-3
	0.0296	4%	Nickel	7440-02-0
	0.0023	0.8%	Copper	7440-50-8
	0.000822	0.5%	Sulphur	7704-34-9
	0	0.000394g max	Carbon (impurity only)	7440-44-0
	0	0.00329g max	Silicon (impurity only)	7440-21-3
	0	0.00658g max	Manganese (impurity only)	7439-96-5
	0	0.000198g max	Phosphorus (impurity only)	7723-14-0
	0	0.00329g max	Molybdenum (impurity only)	7439-98-7
	0	0.000362g max	Nitrogen (impurity only)	7727-37-9
	0	0.000658g max	Niobium (impurity only)	7440-03-1
	0	0.00033g max	Titanium (impurity only)	7440-32-6
Moulding (total weight)	(0.0162 * XX) + 0.135	5%	30% GF Nylon 4T	
Containing:	(0.00907 * XX) + 0.0756	5%	Nylon 4T	103945-40-0
	(0.00486 * XX) + 0.0405	5%	30% Glass Fibre	65997-17-3
	(0.00203 * XX) + 0.0169	5%	Organic phosphorus compound	-
	(0.000243 * XX) + 0.00203	5%	Other Additives	-
Does not contain:			Antimony	
			Other Brominated Flame Retardants	
			Red Phosphorus	

Material Declaration for G125-224XX96XX

Product Information	
Part Number:	G125-224XX96F3
Part Description:	Gecko 1.25mm Female
Part Weight (g):	(0.0162 * XX) + 0.699


Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	n/a
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Screw-Lok Fixings - Stainless Steel	0.407	10%	Iron	7439-89-6
	0.101	4%	Chromium (Metallic)	7440-47-3
	0.0503	4%	Nickel	7440-02-0
	0.00391	0.8%	Copper	7440-50-8
	0.0014	0.5%	Sulphur	7704-34-9
	0	0.00067g max	Carbon (impurity only)	7440-44-0
	0	0.00559g max	Silicon (impurity only)	7440-21-3
	0	0.0112g max	Manganese (impurity only)	7439-96-5
	0	0.000336g max	Phosphorus (impurity only)	7723-14-0
	0	0.00559g max	Molybdenum (impurity only)	7439-98-7
	0	0.000614g max	Nitrogen (impurity only)	7727-37-9
	0	0.00112g max	Niobium (impurity only)	7440-03-1
	0	0.00056g max	Titanium (impurity only)	7440-32-6
Moulding (total weight)	(0.0162 * XX) + 0.135	5%	30% GF Nylon 4T	
Containing:	(0.00907 * XX) + 0.0756	5%	Nylon 4T	103945-40-0
	(0.00486 * XX) + 0.0405	5%	30% Glass Fibre	65997-17-3
	(0.00203 * XX) + 0.0169	5%	Organic phosphorus compound	-
	(0.000243 * XX) + 0.00203	5%	Other Additives	-
Does not contain:			Antimony	
			Other Brominated Flame Retardants	
			Red Phosphorus	

Product Information	
Part Number:	G125-224XX9600
Part Description:	Gecko 1.25mm Female
Part Weight (g):	(0.0162 * XX) + 0.135

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	n/a
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Moulding (total weight)	(0.0162 * XX) + 0.135	5%	30% GF Nylon 4T	
Containing:	(0.00907 * XX) + 0.0756	5%	Nylon 4T	103945-40-0
	(0.00486 * XX) + 0.0405	5%	30% Glass Fibre	65997-17-3
	(0.00203 * XX) + 0.0169	5%	Organic phosphorus compound	-
	(0.000243 * XX) + 0.00203	5%	Other Additives	-
Does not contain:			Antimony	
			Other Brominated Flame Retardants	
			Red Phosphorus	

Prepared by: 

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of: 