

# Material Declaration for G125-FC3XX05L0-YYYYF

Product Information	
Part Number:	G125-FC3XX05L0-YYYYF
Part Description:	2 Female Crimped Conns. with 30AWG Wires
Part Weight (g):	(0.0542 * XX) + (0.00123 * XX * YYYY) + 0.0756

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	Gold
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Beryllium Copper	0.0268 * XX	1%	Copper	7440-50-8
	0.00052 * XX	0.5%	Beryllium	7440-41-7
	0.0011 * XX	0.5%	Lead	7439-92-1
	0	(0.000082 * XX)g max	Nickel (impurity only)	7440-02-0
	0	(0.000054 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000054 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.000082 * XX)g max	Cobalt (impurity only)	7440-48-4
	0	(0.000054 * XX)g max	Silicon (impurity only)	7440-21-3
	0	(0.000136 * XX)g max	Other Impurities	
Contacts - Plating	0.000204 * XX	5%	Gold	7440-57-5
	0.00075 * XX	10%	Nickel	7440-02-0
Moulding (total weight)	(0.0248 * XX) + 0.0756	5%	30% GF Nylon 4T	
Containing:	(0.0139 * XX) + 0.0423	5%	Nylon 4T	103945-40-0
	(0.00744 * XX) + 0.0227	5%	30% Glass Fibre	65997-17-3
	(0.0031 * XX) + 0.00945	5%	Organic phosphorus compound	-
	(0.000372 * XX) + 0.00113	5%	Other Additives	-
Does not contain:			Antimony	
			Other Brominated Flame Retardants	
			Red Phosphorus	
Wire	0.000312 * XX * YYYY	10%	Copper	7440-50-8
Wire - Plating	0.000037 * XX * YYYY	10%	Silver	7440-22-4
Wire - Insulation	0.00088 * XX * YYYY	10%	PTFE	9002-84-0

Prepared by: *M. J. Perry*

Martin J Perry, BSc(Eng) MSc CEng MIET  
 Compliance Specialist  
 ComplianceTeam@harwin.co.uk

On behalf of: **HARWIN**