

Material Declaration for G125-MC2XX05L0-YYYYL

Product Information	
Part Number:	G125-MC2XX05L0-YYYYL
Part Description:	Male Crimped Conn. with 28AWG Wires
Part Weight (g):	(0.0334 * XX) + (0.00157 * XX * YYYY) + 0.0544

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	Gold
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Brass	0.0099 * XX	1%	Copper	7440-50-8
	0.0062 * XX	0.5%	Zinc	7440-66-6
	0.00033 * XX	0.5%	Lead	7439-92-1
	0	(0.000048 * XX)g max	Nickel (impurity only)	7440-02-0
	0	(0.000032 * XX)g max	Iron (impurity only)	7439-89-6
Contacts - Plating	0	(0.000008 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.000032 * XX)g max	Tin (impurity only)	7440-31-5
	0	(0.000032 * XX)g max	Other Impurities	
	0.000087 * XX	5%	Gold	7440-57-5
	0.000321 * XX	10%	Nickel	7440-02-0
Moulding (total weight)	(0.0166 * XX) + 0.0544	5%	30% GF Nylon 4T	
Containing:	(0.0093 * XX) + 0.0305	5%	Nylon 4T	103945-40-0
	(0.00498 * XX) + 0.0163	5%	30% Glass Fibre	65997-17-3
	(0.00208 * XX) + 0.0068	5%	Organic phosphorus compound	-
	(0.000249 * XX) + 0.000816	5%	Other Additives	-
Does not contain:			Antimony	
			Other Brominated Flame Retardants	
			Red Phosphorus	
Wire	0.0005 * XX * YYYY	10%	Copper	7440-50-8
Wire - Plating	0.000059 * XX * YYYY	10%	Silver	7440-22-4
Wire - Insulation	0.00101 * XX * YYYY	10%	PTFE	9002-84-0

Prepared by:

M. J. Perry

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of:

HARWIN