

Material Declaration for G125-MC2XX05L0-YYYYM

Product Information	
Part Number:	G125-MC2XX05L0-YYYYM
Part Description:	2 x Male Crimped Conn. with 28AWG Wires
Part Weight (g):	(0.0669 * XX) + (0.00157 * XX * YYYY) + 0.109

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	Gold
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Brass	0.0198 * XX	1%	Copper	7440-50-8
	0.0124 * XX	0.5%	Zinc	7440-66-6
	0.00066 * XX	0.5%	Lead	7439-92-1
	0	(0.000096 * XX)g max	Nickel (impurity only)	7440-02-0
	0	(0.000064 * XX)g max	Iron (impurity only)	7439-89-6
Contacts - Plating	0	(0.000016 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.000064 * XX)g max	Tin (impurity only)	7440-31-5
	0	(0.000064 * XX)g max	Other Impurities	
	0.000174 * XX	5%	Gold	7440-57-5
	0.000642 * XX	10%	Nickel	7440-02-0
Moulding (total weight)	(0.0332 * XX) + 0.109	5%	30% GF Nylon 4T	
Containing:	(0.0186 * XX) + 0.061	5%	Nylon 4T	103945-40-0
	(0.00996 * XX) + 0.0326	5%	30% Glass Fibre	65997-17-3
	(0.00416 * XX) + 0.0136	5%	Organic phosphorus compound	-
	(0.000498 * XX) + 0.00163	5%	Other Additives	-
			Antimony	
Does not contain:			Other Brominated Flame Retardants	
			Red Phosphorus	
Wire	0.0005 * XX * YYYY	10%	Copper	7440-50-8
Wire - Plating	0.000059 * XX * YYYY	10%	Silver	7440-22-4
Wire - Insulation	0.00101 * XX * YYYY	10%	PTFE	9002-84-0

Prepared by:

M. J. Perry

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of:

HARWIN