


# Material Declaration for M80-5000000M1-XX-331-00-000

Product Information	
Part Number:	M80-5000000M1-XX-331-00-000
Part Description:	Datamate Mix-Tek Male Vertical
Part Weight (g):	(0.316 * XX) + 0.625

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	Gold over Nickel
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Power Contact - Beryllium Copper	0.235 * XX	4%	Copper	7440-50-8
	0.00457 * XX	2%	Beryllium	7440-41-7
	0.000962 * XX	2%	Lead	7439-92-1
	0	(0.000721 * XX)g max	Nickel (impurity only)	7440-02-0
	0	(0.000721 * XX)g max	Cobalt (impurity only)	7440-48-4
	0	(0.000481 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000481 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.000481 * XX)g max	Silicon (impurity only)	7440-21-3
	0	(0.0012 * XX)g max	Other Impurities	
Power Contact - Plating	0.000524 * XX	5%	Gold	7440-57-5
	0.0013 * XX	10%	Nickel	7440-02-0
Jackscrews - Stainless Steel	0.233	10%	Iron	7439-89-6
	0.059	4%	Chromium (Metallic)	7440-47-3
	0.0295	4%	Nickel	7440-02-0
	0.00524	0.8%	Copper	7440-50-8
	0.00082	0.5%	Sulphur	7704-34-9
	0	0.000262g max	Carbon (impurity only)	7440-44-0
	0	0.00328g max	Silicon (impurity only)	7440-21-3
	0	0.00655g max	Manganese (impurity only)	7439-96-5
	0	0.000148g max	Phosphorus (impurity only)	7723-14-0
	0	0.00197g max	Molybdenum (impurity only)	7439-98-7
	0	0.00036g max	Nitrogen (impurity only)	7727-37-9
Moulding (total weight)	(0.0733 * XX) + 0.297	10%	30% Glass-Filled PPS	
Containing:	(0.0513 * XX) + 0.208	10%	PPS	26125-40-6
	(0.022 * XX) + 0.0891	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	

Prepared by: 

Martin J Perry, BSc(Eng) MSc CEng MIET  
 Compliance Specialist  
 ComplianceTeam@harwin.co.uk

On behalf of: 