

Material Declaration for M80-5L2XXXXMD

Product Information	
Part Number:	M80-5L2XX05MD
Part Description:	2mm Horiz Datamate
Part Weight (g):	(0.0465 * XX) + 1.634

Process Data	
Peak Reflow (Deg. C)	260°C for 10 sec
Termination Finish	Gold over Nickel
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #	
Contacts - Phosphor Bronze	0.0221 * XX	5%	Copper	7440-50-8	
	0.00116 * XX	2%	Tin	7440-31-5	
	0.000044 * XX	0.5%	Phosphorus	7723-14-0	
	0	(0.00007 * XX)g max	Zinc (impurity only)	7440-66-6	
	0	(0.000024 * XX)g max	Iron (impurity only)	7439-89-6	
	0	(0.000012 * XX)g max	Lead (impurity only)	7439-92-1	
Contacts - Plating	0	(0.000117 * XX)g max	Other Impurities		
	0.000312 * XX	5%	Gold	7440-57-5	
Jackscrews - Stainless Steel	0.000244 * XX	10%	Nickel	7440-02-0	
	0.639	5%	Iron	7439-89-6	
	0.158	2%	Chromium (Metallic)	7440-47-3	
	0.0791	2%	Nickel	7440-02-0	
	0.0022	0.5%	Sulphur	7704-34-9	
	0	0.00105g max	Carbon (impurity only)	7440-44-0	
	0	0.00879g max	Silicon (impurity only)	7440-21-3	
	0	0.0176g max	Manganese (impurity only)	7439-96-5	
	0	0.000528g max	Phosphorus (impurity only)	7723-14-0	
	0	0.00879g max	Molybdenum (impurity only)	7439-98-7	
	0	0.00176g max	Niobium (impurity only)	7440-03-1	
	0	0.00088g max	Titanium (impurity only)	7440-32-6	
	0	0.00615g max	Copper (impurity only)	7440-50-8	
	Jackscrew Bolts - Stainless Steel	0.326	10%	Iron	7439-89-6
0.0806		4%	Chromium (Metallic)	7440-47-3	
0.0403		4%	Nickel	7440-02-0	
0.00112		0.5%	Sulphur	7704-34-9	
0		0.000538g max	Carbon (impurity only)	7440-44-0	
0		0.00448g max	Silicon (impurity only)	7440-21-3	
0		0.00896g max	Manganese (impurity only)	7439-96-5	
0		0.000268g max	Phosphorus (impurity only)	7723-14-0	
0		0.00448g max	Molybdenum (impurity only)	7439-98-7	
0		0.000896g max	Niobium (impurity only)	7440-03-1	
0		0.000448g max	Titanium (impurity only)	7440-32-6	
0		0.00313g max	Copper (impurity only)	7440-50-8	
Moulding (total weight)		(0.0226 * XX) + 0.308	10%	30% Glass-Filled PPS	
Containing:		(0.0158 * XX) + 0.216	10%	PPS	26125-40-6
	(0.00678 * XX) + 0.0924	10%	30% Glass Fibre	65997-17-3	
Does not contain:			Antimony		
			Other Brominated Flame Retardants		

Material Declaration for M80-5L2XXXXMD

Product Information	
Part Number:	M80-5L2XX22MD
Part Description:	2mm Horiz Datamate
Part Weight (g):	(0.0465 * XX) + 1.634

Process Data	
Peak Reflow (Deg. C)	235°C for 5 sec
Termination Finish	Tin/Lead over Nickel
RoHS Compliant? (Y/N)	No

Note: RoHS compliant by threshold values, lead intentionally added, not recommended for Lead-Free Soldering.

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Phosphor Bronze	0.0221 * XX	5%	Copper	7440-50-8
	0.00116 * XX	2%	Tin	7440-31-5
	0.000044 * XX	0.5%	Phosphorus	7723-14-0
	0	(0.00007 * XX)g max	Zinc (impurity only)	7440-66-6
	0	(0.000024 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000012 * XX)g max	Lead (impurity only)	7439-92-1
Contacts - Plating	0	(0.000117 * XX)g max	Other Impurities	
	0.000066 * XX	5%	Gold	7440-57-5
	0.000281 * XX	5%	Tin	7440-31-5
	0.000049 * XX	5%	Lead	7439-92-1
Jackscrews - Stainless Steel	0.000244 * XX	10%	Nickel	7440-02-0
	0.639	5%	Iron	7439-89-6
	0.158	2%	Chromium (Metallic)	7440-47-3
	0.0791	2%	Nickel	7440-02-0
	0.0022	0.5%	Sulphur	7704-34-9
	0	0.00105g max	Carbon (impurity only)	7440-44-0
	0	0.00879g max	Silicon (impurity only)	7440-21-3
	0	0.0176g max	Manganese (impurity only)	7439-96-5
	0	0.000528g max	Phosphorus (impurity only)	7723-14-0
	0	0.00879g max	Molybdenum (impurity only)	7439-98-7
	0	0.00176g max	Niobium (impurity only)	7440-03-1
	0	0.00088g max	Titanium (impurity only)	7440-32-6
0	0.00615g max	Copper (impurity only)	7440-50-8	
Jackscrew Bolts - Stainless Steel	0.326	10%	Iron	7439-89-6
	0.0806	4%	Chromium (Metallic)	7440-47-3
	0.0403	4%	Nickel	7440-02-0
	0.00112	0.5%	Sulphur	7704-34-9
	0	0.000538g max	Carbon (impurity only)	7440-44-0
	0	0.00448g max	Silicon (impurity only)	7440-21-3
	0	0.00896g max	Manganese (impurity only)	7439-96-5
	0	0.000268g max	Phosphorus (impurity only)	7723-14-0
	0	0.00448g max	Molybdenum (impurity only)	7439-98-7
	0	0.000896g max	Niobium (impurity only)	7440-03-1
	0	0.000448g max	Titanium (impurity only)	7440-32-6
	0	0.00313g max	Copper (impurity only)	7440-50-8
Moulding (total weight)	(0.0226 * XX) + 0.308	10%	30% Glass-Filled PPS	
Containing:	(0.0158 * XX) + 0.216	10%	PPS	26125-40-6
	(0.00678 * XX) + 0.0924	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	


Material Declaration for M80-5L2XXXXMD

Product Information	
Part Number:	M80-5L2XX42MD
Part Description:	2mm Horiz Datamate
Part Weight (g):	(0.0465 * XX) + 1.634

Process Data	
Peak Reflow (Deg. C)	260°C for 10 sec
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #	
Contacts - Phosphor Bronze	0.0221 * XX	5%	Copper	7440-50-8	
	0.00116 * XX	2%	Tin	7440-31-5	
	0.000044 * XX	0.5%	Phosphorus	7723-14-0	
	0	(0.00007 * XX)g max	Zinc (impurity only)	7440-66-6	
	0	(0.000024 * XX)g max	Iron (impurity only)	7439-89-6	
Contacts - Plating	0	(0.000012 * XX)g max	Lead (impurity only)	7439-92-1	
	0	(0.000117 * XX)g max	Other Impurities		
	0.000066 * XX	5%	Gold	7440-57-5	
	0.000313 * XX	5%	Tin	7440-31-5	
	0.000244 * XX	10%	Nickel	7440-02-0	
Jackscrews - Stainless Steel	0.639	5%	Iron	7439-89-6	
	0.158	2%	Chromium (Metallic)	7440-47-3	
	0.0791	2%	Nickel	7440-02-0	
	0.0022	0.5%	Sulphur	7704-34-9	
	0	0.00105g max	Carbon (impurity only)	7440-44-0	
	0	0.00879g max	Silicon (impurity only)	7440-21-3	
	0	0.0176g max	Manganese (impurity only)	7439-96-5	
	0	0.000528g max	Phosphorus (impurity only)	7723-14-0	
	0	0.00879g max	Molybdenum (impurity only)	7439-98-7	
	0	0.00176g max	Niobium (impurity only)	7440-03-1	
	0	0.00088g max	Titanium (impurity only)	7440-32-6	
	0	0.00615g max	Copper (impurity only)	7440-50-8	
	Jackscrew Bolts - Stainless Steel	0.326	10%	Iron	7439-89-6
		0.0806	4%	Chromium (Metallic)	7440-47-3
		0.0403	4%	Nickel	7440-02-0
0.00112		0.5%	Sulphur	7704-34-9	
0		0.000538g max	Carbon (impurity only)	7440-44-0	
0		0.00448g max	Silicon (impurity only)	7440-21-3	
0		0.00896g max	Manganese (impurity only)	7439-96-5	
0		0.000268g max	Phosphorus (impurity only)	7723-14-0	
0		0.00448g max	Molybdenum (impurity only)	7439-98-7	
0		0.000896g max	Niobium (impurity only)	7440-03-1	
0		0.000448g max	Titanium (impurity only)	7440-32-6	
0		0.00313g max	Copper (impurity only)	7440-50-8	
Moulding (total weight)		(0.0226 * XX) + 0.308	10%	30% Glass-Filled PPS	
Containing:		(0.0158 * XX) + 0.216	10%	PPS	26125-40-6
		(0.00678 * XX) + 0.0924	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony		
			Other Brominated Flame Retardants		

Prepared by:  M. J. Perry

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Specialist
ComplianceTeam@harwin.co.uk

On behalf of:  **HARWIN**