

## Material Declaration for M83-LFT1F2NXX-0000-000

Product Information	
Part Number:	M83-LFT1F2NXX-0000-000
Part Description:	2mm PC Tail Datamate
Part Weight (g):	(0.0764 * XX) + 1.596

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	Gold over Nickel/Copper
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contact Shell - Brass	0.0296 * XX	2%	Copper	7440-50-8
	0.0165 * XX	1%	Zinc	7440-66-6
	0.00141 * XX	0.5%	Lead	7439-92-1
	0	(0.000141 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000141 * XX)g max	Tin (impurity only)	7440-31-5
	0	(0.000141 * XX)g max	Nickel (impurity only)	7440-02-0
	0	(0.000024 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.000246 * XX)g max	Other Impurities	
Contact Shell - Plating	0.000212 * XX	5%	Gold	7440-57-5
	0.000525 * XX	10%	Nickel	7440-02-0
	0.000438 * XX	10%	Copper	7440-50-8
Contact Clip - Beryllium Copper	0.00207 * XX	1%	Copper	7440-50-8
	0.00004 * XX	0.5%	Beryllium	7440-41-7
	0	(0.000006 * XX)g max	Nickel (impurity only)	7440-02-0
	0	(0.000006 * XX)g max	Cobalt (impurity only)	7440-48-4
	0	(0.000004 * XX)g max	Iron (impurity only)	7439-89-6
	0	(0.000004 * XX)g max	Aluminium (impurity only)	7429-90-5
	0	(0.000004 * XX)g max	Silicon (impurity only)	7440-21-3
	0	(0.000011 * XX)g max	Other Impurities	
Contact Clip - Plating	0.000058 * XX	10%	Nickel	7440-02-0
	0.000006 * XX	5%	Gold	7440-57-5
Jackscrew Retaining Collar - Brass	0.169	2%	Copper	7440-50-8
	0.114	1%	Zinc	7440-66-6
	0.00876	0.5%	Lead	7439-92-1
	0	0.000876g max	Iron (impurity only)	7439-89-6
	0	0.000876g max	Tin (impurity only)	7440-31-5
	0	0.000876g max	Nickel (impurity only)	7440-02-0
	0	0.000146g max	Aluminium (impurity only)	7429-90-5
	0	0.000584g max	Other Impurities	
Jackscrew Retaining Collar - Plating	0.00209	20%	Nickel	7440-02-0
Jackscrew Bolts - Stainless Steel	0.573	10%	Iron	7439-89-6
	0.142	4%	Chromium (Metallic)	7440-47-3
	0.0709	4%	Nickel	7440-02-0
	0.00552	0.8%	Copper	7440-50-8
	0.00197	0.5%	Sulphur	7704-34-9
	0	0.000946g max	Carbon (impurity only)	7440-44-0
	0	0.00788g max	Silicon (impurity only)	7440-21-3
	0	0.0158g max	Manganese (impurity only)	7439-96-5
	0	0.000472g max	Phosphorus (impurity only)	7723-14-0
	0	0.00788g max	Molybdenum (impurity only)	7439-98-7
	0	0.00158g max	Niobium (impurity only)	7440-03-1
	0	0.000788g max	Titanium (impurity only)	7440-32-6
Moulding (total weight)	(0.0255 * XX) + 0.509	10%	30% Glass-Filled PPS	
Containing:	(0.0179 * XX) + 0.356	10%	PPS	26125-40-6
	(0.00765 * XX) + 0.153	10%	30% Glass Fibre	65997-17-3
Does not contain:			Antimony	
			Other Brominated Flame Retardants	

Prepared by: *M. J. Perry*

Martin J Perry, BSc(Eng) MSc CEng MIET  
Compliance Specialist  
ComplianceTeam@harwin.co.uk

On behalf of: **HARWIN**