

## Material composition for W2530-00

| Product Information |                  |
|---------------------|------------------|
| Part Number:        | W2530-00         |
| Part Description:   | Insulated Turret |
| Part Weight (g):    | 0.318            |

| Process Data          |                      |
|-----------------------|----------------------|
| Peak Reflow (Deg. C)  | 260°C for 10 sec     |
| MSL                   | 1                    |
| Lead Finish           | 100% Tin over Nickel |
| RoHS Compliant Mark   | n/a                  |
| Availability Date     | Now                  |
| RoHS Compliant? (Y/N) | Yes (exemption 6c)   |

| Homogeneous Material Location   | Weight(g) | Tolerance                           | Substance Name    | CAS #      |
|---------------------------------|-----------|-------------------------------------|-------------------|------------|
| Turret Contact - Brass          | 0.043     | 2%                                  | Copper            | 7440-50-8  |
|                                 | 0.0289    | 1%                                  | Zinc              | 7440-66-6  |
|                                 | 0.00223   | 0.50%                               | Lead              | 7439-92-1  |
|                                 | 0         | 0.000223g max                       | Iron              | 7439-89-6  |
|                                 | 0         | 0.000223g max                       | Tin               | 7440-31-5  |
|                                 | 0         | 0.000223g max                       | Nickel            | 7440-02-0  |
|                                 | 0         | 0.000037g max                       | Aluminium         | 7429-90-5  |
| Turret Contact - Plating        | 0         | 0.000148g max                       | Impurities        |            |
|                                 | 0.00212   | 5%                                  | Tin               | 7440-31-5  |
|                                 | 0.000687  | 10%                                 | Nickel            | 7440-02-0  |
| Female Thread Contact - Brass   |           |                                     |                   |            |
|                                 | 0.0587    | 2%                                  | Copper            | 7440-50-8  |
|                                 | 0.0394    | 1%                                  | Zinc              | 7440-66-6  |
|                                 | 0.00303   | 0.50%                               | Lead              | 7439-92-1  |
|                                 | 0         | 0.000303g max                       | Iron              | 7439-89-6  |
|                                 | 0         | 0.000303g max                       | Tin               | 7440-31-5  |
|                                 | 0         | 0.000303g max                       | Nickel            | 7440-02-0  |
| Female Thread Contact - Plating | 0         | 0.000051g max                       | Aluminium         | 7429-90-5  |
|                                 | 0         | 0.000202g max                       | Impurities        |            |
|                                 | 0.00117   | 10%                                 | Nickel            | 7440-02-0  |
| Moulding (total weight)         | 0.138     | 5%                                  | 30% GF PA46       | 50327-22-5 |
| Containing:                     | 0.0414    | 5%                                  | 30% Glass Fibre   | 65997-17-3 |
|                                 | >1000ppm  |                                     | Antimony Trioxide | 1309-64-4  |
|                                 | >1000ppm  | Other Brominated Flame Retardant(s) |                   |            |
|                                 |           |                                     |                   |            |

Prepared by: *Wendy Preston*

Mrs Wendy Jane Preston, BEng (Hons)  
Legislation Officer  
leadfree@harwin.co.uk

On behalf of:

**HARWIN**